## DOW CORNING CORPORATION Material Safety Data Sheet

Page: 1 of 7 Version: 1.5 Revision Date: 2011/01/28

# MOLYKOTE(R) 111 COMPOUND

### 1. PRODUCT AND COMPANY IDENTIFICATION

Dow Corning Corporation South Saginaw Road Midland, Michigan 48686 **24 Hour Emergency Telephone:** (989) 496-5900 Customer Service: (989) 496-6000 Product Disposal Information: (989) 496-6315 CHEMTREC: (800) 424-9300

MSDS No.: 01889834

Revision Date: 2011/01/28

Generic Description: Silicone grease. Physical Form: Grease Color: Translucent white Odor: Odorless

NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

#### 2. HAZARDS IDENTIFICATION

#### POTENTIAL HEALTH EFFECTS

#### Acute Effects

Eye:	Direct contact may cause temporary redness and discomfort.		
Skin:	No significant irritation expected from a single short-term exposure.		
Inhalation:	No significant effects expected from a single short-term exposure.		
Oral:	Low ingestion hazard in normal use.		
Prolonged/Repeated Exposure Effects			
Skin:	No known applicable information.		
Inhalation:	No known applicable information.		
Oral:	No known applicable information.		
Signs and Symptoms of Overexposure			
No known applicable information.			
Medical Conditions Aggravated by Exposure			
No known applicable int	No known applicable information.		
1			

## DOW CORNING CORPORATION Material Safety Data Sheet

Page: 2 of 7 Version: 1.5 Revision Date: 2011/01/28

# MOLYKOTE(R) 111 COMPOUND

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

None present. This is not a hazardous material as defined in the OSHA Hazard Communication Standard.

# 4. FIRST AID MEASURES Eye: If irritation occurs, flush eye(s) with lukewarm gently flowing water for 5 minutes. Obtain medical attention. Skin: No health effects expected. If irritation does occur flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice. Inhalation: If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice. Oral: If irritation or discomfort occur, obtain medical advice. Notes to Physician: Treat according to person's condition and specifics of exposure.

5. FIRE FIGHTING MEASURES		
Flash Point:	> 214 °F / > 101.1 °C (Closed Cup)	
Autoignition Temperature:	Not determined.	
Flammability Limits in Air:	Not determined.	
Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO2), dry chemical or water spray. Water can be used to cool fire exposed containers.	
Fire Fighting Measures:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.	
Unusual Fire Hazards:	None.	

#### 6. ACCIDENTAL RELEASE MEASURES

## DOW CORNING CORPORATION Material Safety Data Sheet

Page: 3 of 7 Version: 1.5 Revision Date: 2011/01/28

# MOLYKOTE(R) 111 COMPOUND

Containment/Clean up: Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See Section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

#### 7. HANDLING AND STORAGE

Use with adequate ventilation. Avoid eye contact.

Use reasonable care and store away from oxidizing materials. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Component Exposure Limits**

There are no components with workplace exposure limits.

#### **Engineering Controls**

Local Ventilation:None should be needed.General Ventilation:Recommended.

#### Personal Protective Equipment for Routine Handling

Personal Protective Equipment for Spills	
Suitable Respirator:	None should be needed.
Inhalation:	No respiratory protection should be needed.
Suitable Gloves:	Handle in accordance with good industrial hygiene and safety practices.
Skin:	Washing at mealtime and end of shift is adequate.
Eyes:	Use proper protection - safety glasses as a minimum.

#### Personal Protective Equipment for Spills

Respirator:

## DOW CORNING CORPORATION **Material Safety Data Sheet**

Page: 4 of 7 Version: 1.5 Revision Date: 2011/01/28

# **MOLYKOTE(R) 111 COMPOUND**

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Washing at mealtime and end of shift is adequate.

Inhalation/Suitable No respiratory protection should be needed.

Precautionary Measures: Avoid eye contact. Use reasonable care.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Color:	Grease Translucent white
Odor:	Odorless
Specific Gravity @ 25°C:	1.1
Viscosity:	Not determined.
Freezing/Melting Point:	Not determined.
	Not determined.
Vapor Pressure @ 25°C:	Not determined.
Vapor Density:	Not determined.
Solubility in Water:	Not determined.
pH:	Not determined.
Volatile Content:	Not determined.
Flash Point:	> 214 °F / > 101.1 °C (Closed Cup)
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND R	10. STABILITY AND REACTIVITY		
Chemical Stability:	Stable.		
Hazardous Polymerization:	Hazardous polymerization will not occur.		
Conditions to Avoid:	None.		
Materials to Avoid:	Oxidizing material can cause a reaction.		
Hazardous Decomposition Products			
Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon ovides and traces of incompletely burned carbon compounds. Silicon dioxide, Formaldebyde			

products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde.



## DOW CORNING CORPORATION Material Safety Data Sheet

Page: 5 of 7 Version: 1.5 Revision Date: 2011/01/28

# MOLYKOTE(R) 111 COMPOUND

#### 11. TOXICOLOGICAL INFORMATION

#### **Special Hazard Information on Components**

No known applicable information.

#### **12. ECOLOGICAL INFORMATION**

#### **Environmental Fate and Distribution**

Complete information is not yet available.

#### **Environmental Effects**

Complete information is not yet available.

#### Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

**Ecotoxicity Classification Criteria** 

Hazard Parameters (LC50 or EC50)	High	Medium	Low	
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100	
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000	
This table is adapted from "Environmental Taviagle	au and Diale Assass	ant ACTM CTD 1170 - 24 1002		

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

#### **13. DISPOSAL CONSIDERATIONS**

#### RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal. Call (989) 496-6315, if additional information is required.

#### 14. TRANSPORT INFORMATION

#### DOT Road Shipment Information (49 CFR 172.101)

Not subject to DOT.

**Ocean Shipment (IMDG)** 

## DOW CORNING CORPORATION Material Safety Data Sheet

Page: 6 of 7 Version: 1.5 Revision Date: 2011/01/28

# MOLYKOTE(R) 111 COMPOUND

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

#### **15. REGULATORY INFORMATION**

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

#### EPA SARA Title III Chemical Listings

Section 302 Extremely Hazardous Substances (40 CFR 355): None.

Section 304 CERCLA Hazardous Substances (40 CFR 302): None.

#### Section 311/312 Hazard Class (40 CFR 370):

Acute: No Chronic: No Fire: No Pressure: No Reactive: No

#### Section 313 Toxic Chemicals (40 CFR 372):

None present or none present in regulated quantities.

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

#### Supplemental State Compliance Information

#### California

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

Massachusetts

## DOW CORNING CORPORATION Material Safety Data Sheet

Page: 7 of 7 Version: 1.5 Revision Date: 2011/01/28

# MOLYKOTE(R) 111 COMPOUND

	CAS Number	<u>Wt %</u>	Component Name
	7631-86-9	7.0 - 13.0	Silica, amorphous
	New Jersey		
	New Jeisey		
	CAS Number	<u>Wt %</u>	Component Name
	63148-62-9	70.0 - 90.0	Polydimethylsiloxane
	7631-86-9	7.0 - 13.0	Silica, amorphous
	70131-67-8	5.0 - 10.0	Dimethyl siloxane, hydroxy-terminated
	Pennsylvania		
	CAS Number	<u>Wt %</u>	Component Name
	63148-62-9	70.0 - 90.0	Polydimethylsiloxane
	7631-86-9	7.0 - 13.0	Silica, amorphous
	70131-67-8	5.0 - 10.0	Dimethyl siloxane, hydroxy-terminated
L			

#### **16. OTHER INFORMATION**

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark