exocet

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH)

XO1482TA Exocet Cooker Additive

SECTION 1: Identification of the substance/mixture and of the company/undertaking

_	_	_	 _			_ 4			_	-		•	, _	
п	۱.1	_	~	Ν.		ct	- 1	~	$\boldsymbol{\sim}$	•		•	\sim	
	_	_	 . Ju				- 11							
		•	•	,	•	•		•	•	•	•		•	•

Product name: XO1482TA Exocet Cooker Additive (*new formulation*)

Trade name(s): Exocet Cooker Additive (XO1482TA)

Product description: Liquid fuel additive

CAS No.:

EC No.:

Index No.:

Not applicable.

Not applicable.

Not applicable.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s): Liquid fuel additive.

Uses advised against: Follow supplier's recommendations on correct use of the

product.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Fuel Additive Science Technologies Limited

Unit 29, Atcham Business Park, Upton Magna, Shrewsbury, Shropshire, SY4 4UG

Telephone: +44 1743 761415

E-mail: info@fastexocet.co.uk

1.4 Emergency telephone number

In case of emergency, call: 0844 560 5135 (24 hours, 7 days)

exocet

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH)

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No. 1272/2008 (CLP)

Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Dam. 1; H318 Carc. 2; H351

Aquatic Acute 1; H400 Aquatic Chronic 1; H410

2.1.2. Classification according to Directive 67/548/EEC & Directive 1999/45/EC

Irritant; Xi; R38 Irritant; Xi; R41 Carc. Cat. 3; R40 Harmful; Xn; R65

Dangerous for the environment; N; R50/53

2.2 Label elements

2.2.1. Label according to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictogram(s):



Signal Word: Danger.

Hazard Statement(s): H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H318: Causes serious eye damage. H351: Suspected of causing cancer.

H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statement(s): P280: Wear protective gloves / protective clothing / eye

protection / face protection.



According to Regulation (EC) No. 1907/2006 (REACH)

P301 + P310: IF SWALLOWED: Immediately call a

POISON CENTER or doctor/physician.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER or

doctor/physician.

P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container to: disposal should be in accordance with local, state or national legislation.

Supplemental Hazard information None. **(EU):**

2.2.2. Label according to Directive 67/548/EEC or Directive 1999/45/EC

Hazard symbol(s):





Indication(s) of danger: Harmful; Dangerous for the Environment.

Risk phrase(s): R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R40: Limited evidence of a carcinogenic effect

R65: Harmful: may cause lung damage if swallowed. R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrase(s): S23: Do not breathe fumes/vapour.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately

with plenty of water and seek medical advice. S62: If swallowed, do not induce vomiting: seek

medical advice immediately and show this container or

label.

S29: Do not empty into drains.



According to Regulation (EC) No. 1907/2006 (REACH)

S35: This material and its container must be disposed

of in a safe way.

S36: Wear suitable protective clothing.

S39: Wear eye/face protection.

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special

instructions/Safety Data Sheets.

2.3 Other hazards

None known.

SECTION 3: Composition

3.2 Mixtures

Classification according to Regulation (EC) No. 1272/2008 (CLP)

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Solvent naphtha (petroleum), heavy arom.	30-40	64742-94-5	265-198-5	649-424-00-3	Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Aquatic Chronic 2; H411
2,6-Di-tert-butylphenol	30-40	128-39-2	204-884-0	-	Eye Dam 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410
Trimethylbenzene	10-20	25551-13-7	247-099-9	-	Flam Liq. 3; H226 Acute Tox 4; H302 Acute Tox 4; H312 Skin Irrit. 2; H315
Naphthalene	5-10	91-20-3	202-049-5	601-052-00-2	Acute Tox 4; H302 Carc 2; H351 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Classification according to Directive 67/548/EEC

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Solvent naphtha (petroleum), heavy arom.	30-40	64742-94-5	265-198-5	649-424-00-3	Xi; R36/38 Xn; R65 N; R51/53



According to Regulation (EC) No. 1907/2006 (REACH)

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
2,6-Di-tert-butylphenol	30-40	128-39-2	204-884-0	-	Xi; R41 N; R50/53
Trimethylbenzene	10-20	25551-13-7	247-099-9	-	R10 Xn; R21/22 Xi; R38
Naphthalene	5-10	91-20-3	202-049-5	601-052-00-2	Xn; R22 Carc. Cat. 3; R40 N; R50/53

See Section 16 for full description of R phrases and H statements.

SECTION 4: First Aid Measures

4.1 Description of first aid measures

INHALATION: Remove patient form exposure, keep warm and at rest.

If symptoms persist, obtain medical attention.

SKIN CONTACT: Remove contaminated clothing immediately. Rinse

affected area with copious amounts of water. Then wash area with soap and water for at least 15 minutes. If symptoms persist, obtain medical attention. Discard of or wash thoroughly contaminated clothing.

EYE CONTACT: Obtain immediate medical attention. Remove contact

lenses if present and easy to do. Wash eyes immediately with plenty of water for at least 30 minutes.

INGESTION: Obtain immediate medical attention. Provided the

patient is conscious wash mouth out with water and provide patient with 200-300 ml of water to drink. Do

not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact causes redness and pain. Eye contact causes burns, watering, redness and pain. Inhalation of high concentrations of vapour may cause irritation to the respiratory tract. Ingestion may cause irritation to mouth, throat and digestive tract. If swallowed, aspiration into lungs may result in chemical pneumonia.

Suspected of causing cancer.



According to Regulation (EC) No. 1907/2006 (REACH)

4.3 Indication of any immediate medical attention and special treatments needed:

In case of accident or if you feel unwell, seek medical advice immediately. If in contact with eyes, wash eyes immediately and seek immediate medical attention. If swallowed, patient should be monitored for signs of breathing difficulty as effects of aspiration may be delayed for up to 48 hours. If breathing is laboured, oxygen should be administered by qualified personnel.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media

Suitable extinguishing media: Foam, CO2 or dry powder.

For large fires, use water.

Unsuitable extinguishing media: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Combustible liquid and vapour. Vapour may form explosive mixture with air.

Combustion may liberate toxic fumes: Carbon monoxide, carbon dioxide, various hydrocarbons.

5.3 Advice for fire-fighters

A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep fire exposed containers cool by spraying with water. Do not allow to enter drains, sewers or watercourses.

Flash point: 65°C (closed cup).

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Eliminate sources of ignition. Ensure adequate ventilation. Avoid breathing fumes/vapour. Avoid contact with skin and eyes. Wear suitable personal protective equipment. Wear appropriate respirator when ventilation is inadequate. (See section 8).

6.1.2 For emergency responders

Keep unnecessary personnel away. Wear suitable protective clothing (See Section 8). Contaminated clothing should be thoroughly cleaned.



According to Regulation (EC) No. 1907/2006 (REACH)

6.2 Environmental precautions

Collect spillage. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

6.3 Methods and materials for containment and clearing up

6.3.1 For containment

Stop the leak if it is safe to do so. Contain the spillage with sand, earth or any suitable adsorbent material.

6.3.2 For cleaning up

Use sand, earth or any suitable non-combustible adsorbent material to adsorb spillages. Using non-sparking tools transfer the contaminated absorbent material into a container for disposal. The containers used should be plastic-lined sealable drums. Containers should be sealed before being disposed of via an authorised waste disposal contractor.

6.3.3 Other advice

None.

6.4 Reference to other sections

See Section 8 for personal protective equipment. See Section 13 for waste disposal.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation, including local extraction to ensure occupational exposure limits are not exceeded. Avoid breathing fumes/vapour. Avoid contact with skin and eyes. Wear suitable personal protective equipment (See Section 8).

Do not eat, drink or smoke in the vicinity of the product. Wash exposed skin after use. Contaminated clothing should be thoroughly cleaned or disposed of as hazardous waste.

7.2 Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Keep from direct sunlight. Store locked up. Store only in the original container. Store in a cool, well ventilated place. Maximum handling temperature: 50°C. Empty containers retain product residue and can be hazardous.

Keep away from oxidising agents.



According to Regulation (EC) No. 1907/2006 (REACH)

7.3 Specific end uses(s)

Liquid fuel additive.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Workplace exposure limits

Source: EH40/2005, 2nd Ed., 2011.

Substance	CAS No.	LTEL (8	hr TWA)	STEL (Comments	
Substance	CAS NO.	ppm	mg/m³	ppm	mg/m³	Comments
Trimethylbenzenes, all isomers or mixtures	25551-13-7	25	125	-	-	-

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Provide adequate ventilation, including local extraction to ensure occupational exposure limits are not exceeded.

8.2.2 Personal protection

Eye protection: Goggles giving complete protection to eyes. (EN 166)

Skin protection:

Hand protection: Chemical resistant gloves. (EN 374).

Other: Long sleeve protective clothing. Plastic apron. Rubber

boots.

Respiratory protection: In the case of insufficient ventilation, wear suitable

respiratory equipment. (BS EN 14387:2004+A1)

Thermal hazards: Wear suitable temperature resistant gloves and

protective clothing if the product is heated.

8.2.3 Environmental exposure controls

Inform environmental manager of all incidents involving this product.



According to Regulation (EC) No. 1907/2006 (REACH)

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:

Odour:

Hydrocarbon.

Odour threshold:

PH:

Not available.

Melting/freezing point::

Initial boiling point and boiling range:

Brown liquid.

Hydrocarbon.

Not available.

Not available.

Flash point: 65°C (Closed cup)

Evaporation rate:

Flammability (solid; gas):

Upper/lower flammability or explosive limits:

Vapour pressure:

Not available.

Not available.

Not available.

Relative density: 0.89 - 0.95 (Water = 1)

Solubility(ies): Immiscible in water.

Miscible in aromatic solvents.

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

Not available.

Not available.

Not available.

Viscosity:

Not available.

Explosive properties: Not explosive. Vapour may form explosive mixture with

air.

Oxidising properties: Not oxidising.

9.2 Other information

None.

SECTION 10: Stability and Reactivity

10.1 Reactivity Reacts with oxidising agents.

10.2 Chemical stability Stable under normal conditions.



According to Regulation (EC) No. 1907/2006 (REACH)

10.3 Possibility of hazardous reactions No hazardous reactions expected during normal use.

10.4 Conditions to avoid Keep away from sources of ignition, hot surfaces and

direct sunlight. Contact with incompatible materials.

10.5 Incompatible materials Oxidising agents.

10.6 Hazardous decomposition products Combustion may liberate toxic fumes: Carbon monoxide,

carbon dioxide, various hydrocarbons.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity May cause discomfort if swallowed.

No data available on the mixture.

Skin corrosion/irritationCauses skin irritation.

Serious eye damage/irritationCauses serious eye damage.

Skin sensitisationNo evidence of skin sensitisation

Respiratory sensitisationNo evidence of respiratory sensitisation.

Germ cell mutagenicityNo evidence of mutagenicity.

Carcinogenicity Suspected of causing cancer.

Reproductive toxicityNo evidence of reproductive toxicity.

Specific Target Organ Toxicity – single

exposure

Inhalation of high concentrations of vapour may cause

irritation to the respiratory tract.

Specific Target Organ Toxicity –

repeated exposure

Based on the available data, the classification criteria

are not met.

Aspiration hazard May be fatal if swallowed and enters airways. Risk of

aspiration into lungs resulting in chemical pneumonia.

Information on likely routes of exposure

Inhalation Inhalation of high concentrations of vapour may cause

irritation to the respiratory tract.



According to Regulation (EC) No. 1907/2006 (REACH)

Skin contact Causes skin irritation.

Eye contact Causes serious eye damage.

Ingestion Ingestion may cause irritation to mouth, throat and

digestive tract. May be fatal if swallowed and enters airways. Risk of aspiration into lungs resulting in

chemical pneumonia.

Symptoms related to the physical, chemical

and toxicological characteristics

Skin contact causes redness and pain. Eve contact causes burns, watering, redness and pain. Inhalation of high concentrations of vapour may cause irritation to the respiratory tract. Ingestion may cause irritation to mouth, throat and digestive tract. If swallowed, aspiration into

The product does not contain substances assessed to

lungs may result in chemical pneumonia.

Mixture versus substance information No data available.

Other information None.

SECTION 12: Ecological Information

12.1 **Toxicity** Very toxic to aquatic life with long lasting effects.

No data available on the mixture.

12.2 Persistence and degradability No data available.

No data available. 12.3 Bioaccumulative potential

12.4 Mobility in soil No data available.

assessment

Results of PBT and vPvB

be PBT or vPvB.

12.6 Other adverse effects None known.

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

To be disposed of as hazardous waste. Disposal should be in accordance with local, state or national legislation.

Version: 2.0 Date: 28/09/2012

12.5



According to Regulation (EC) No. 1907/2006 (REACH)

Contaminated adsorbent must be removed in sealed, plastic lined drums and disposed of via an authorised waste disposal contractor. Do not empty into drains; dispose of this material and its container in a safe way.

SECTION 14: Transport Information

ADR		
14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
ADN		
14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
RID		
14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
IATA	/ICAO	
14.1	UN Number	3082
14.2	UN Proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (contains 2,6-di-tert-butylphenol)

Version: 2.0 Date: 28/09/2012

Transport hazard class(es)

9



According to Regulation (EC) No. 1907/2006 (REACH)

14.4 Packing group14.5 Environmental hazardsYes

14.6 Special precautions for the user Read SDS and supplier instructions on correct use of

the product.

IMDG

14.1 UN Number 3082

14.2 UN Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol)

14.3 Transport hazard class(es)

14.4 Packing group

14.5 Environmental hazards Marine Pollutant

14.6 Special precautions for the user Read SDS and supplier instructions on correct use of

the product.

14.7 Transport in bulk according to Annex II The product is not intended to be transported in bulk.

of MARPOL 73/78 and the IBC code

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 1907/2006 as amended. The product has been classified in accordance with Regulation (EC) No. 1272/2008 (CLP), Directive

67/548/EEC & Directive 1999/45/EC.

15.2 Chemical Safety Assessment Not applicable.

SECTION 16: Other Information

Full text of relevant R-phrases and/or H-statements:

Hazard Statement(s): H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage. H319: Causes serious eye irritation. H351: Suspected of causing cancer.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effect.



According to Regulation (EC) No. 1907/2006 (REACH)

H411: Toxic to aquatic life with long lasting effects.

Supplemental Hazard information None.

(EU):

Risk phrase(s): R10: Flammable.

R21/22: Harmful in contact with skin and if swallowed.

R22: Harmful if swallowed.

R36/38: Irritating to eyes and skin.

R38: Irritating to skin.

R40: Limited evidence of a carcinogenic effect.

R41: Risk of serious damage to eyes.

R65: Harmful: may cause lung damage if swallowed. R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53: Toxic to aquatic organisms, may cause longterm adverse effects in the aquatic environment.

Abbreviations:

CAS: Chemical Abstracts Service:

EINECS: European Inventory of Existing Commercial Chemical Substances

PBT: Persistent, Bioaccumulative and Toxic. vPvB: Very Persistent and Very Bioaccumulative.

References:

Supplier's Safety Data Sheets for ingredients

Product formulation

Approved Classification and Labelling Guide (Sixth edition)

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 Regulation (EC) No. 1272/2008 of the European Parliament and of the council.

EH40/2005, 2nd Ed., 2011.

Disclaimer:

THE INFORMATION PRESENTED HEREIN IS BELIEVED TO BE ACCURATE, BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM, IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

Version history:

Version: 2.0

Issue date: 28/09/2012

Version: 2.0 XO1482TA Exocet Cooker Additive Date: 28/09/2012



According to Regulation (EC) No. 1907/2006 (REACH)

Previous Version: 1.0

Issue date of previous version: 09/05/2012

Sections changed from previous version: 1-16