

DOMUS MAS87 INTUMESCENT ACOUSTIC ACRYLIC MASTIC WATER BASED ACRYLIC SEALANT

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical composition: Aqueous acrylic emulsion and mineral fillers

No component labelled dangerous under EEC Directives criteria

HAZARDS IDENTIFICATION

Low oral toxicity. Prolonged exposure to the product may result in irritation of the skin

FIRST-AID MEASURES

| | |
|------------|--|
| Skin | Wash with soap and water |
| Eye | Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Seek medical attention if any discomfort continues. |
| Ingestion | Give plenty of water to drink. Obtain medical attention. |
| Inhalation | Remove person to fresh air. Seek medical attention if any discomfort continues. |

FIRE FIGHTING MEASURES

| | |
|--|--|
| Extinguishing Media | Water spray jet, dry powder, foam or CO ² |
| Special Exposure Hazard | Not applicable |
| Special Fire-Fighting Protective Equipment | Not applicable |

ACCIDENTAL RELEASE MEASURES

Remove by mechanical means

HANDLING AND STORAGE

| | |
|-------------------|--|
| Usage Precautions | Avoid spilling, skin and eye contact |
| Storage | Keep in cool, dry, ventilated area. Keep in original container |

EXPOSURE CONTROLS/PERSONAL PROTECTION

| Ingredient: | Cas No. | Std | LT Exp 8 Hrs | ST Exp 15 Min |
|--------------|------------|-----|--------------|---------------|
| White Spirit | 64742-82-1 | OES | 600 mg/m3 | |

| | |
|----------------------|---|
| Protective Equipment | Wear protective gloves if risk of skin contact Wear approved safety goggles No particular ventilation requirements Do not smoke in work area |
|----------------------|---|

PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---------------------------|-----------------------|
| Appearance: | Thixotropic paste |
| Colour: | White, Grey |
| Odour/Taste: | Slight |
| Density/Specific Gravity: | 1.65 at 20°C |
| pH Value: | 8 |
| Viscosity: | 7000-10000 Ps at 20oC |
| Solubility: | Miscible with water |

STABILITY AND REACTIVITY

| | |
|----------------------|--|
| Stability: | Normally stable (stored cool) |
| Product Shelf Life: | 12 months |
| Conditions to avoid: | Avoid excessive heat for prolonged periods of time |

TOXICOLOGICAL INFORMATION

This product has low toxicity. Only large volumes may have adverse impact on human health.

Prolonged exposure may result in irritation of the skin

No specific health warnings noted.

ECOLOGICAL INFORMATION

Not regarded as dangerous for the environment

DISPOSAL CONSIDERATIONS

Dispose of in accordance with Local Authority requirements

TRANSPORT REGULATIONS/INFORMATION

Road, Sea, Air Not classified

REGULATORY INFORMATION

Occupational exposure limits EH40, CHIP for everyone HSG (108)

FURTHER INFORMATION

R-PHRASES: R10 Flammable. R51/53 Toxin to aquatic organisms may cause long term adverse effects in the aquatic environment. R-65 Harmful: may cause lung damage if swallowed. R-66 Repeated exposure may cause skin dryness or cracking.

DISCLAIMER: The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.

Polypipe Ventilation
Sandall Stones Road
Kirk Sandall Industrial Park
Doncaster, DN3 1QR
Tel: 08443 715523
Fax: 08443 715524
Email: vent.info@polypipe.com