according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator



BUILDING TRUST

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Everbuild Mitre Fast Activator

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company : Everbuild - A Sika Company

Site 41

Knowsthorpe Way

Cross Green Industrial Estate

West Yorkshire LS9 0SW

United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

1.4 Emergency telephone number

Emergency telephone num-

ber

: 0044 113 240 3456 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation. H336: May cause drowsiness or dizziness.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

Long-term (chronic) aquatic hazard, Cat-

H411: Toxic to aquatic life with long lasting effects.

egory 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word Danger

Revision Date 24.02.2020

according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator





Print Date 24.02.2020

| Hazard statements | : | H222 | Extremely flammable aerosol. |
|-------------------|---|------|------------------------------|

H229 Pressurised container: May burst if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

Version 4.0

P211 Do not spray on an open flame or other igni-

tion source.

P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P273 Avoid release to the environment.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

• Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. | Classification | Concentration | | |
|--|----------------------|---------------------|---------------|--|--|
| | EC-No. | | (% w/w) | | |
| | Registration number | | | | |
| Hydrocarbons, C6-C7, n-alkanes, | Not Assigned | Flam. Liq. 2; H225 | >= 25 - < 40 | | |
| isoalkanes, cyclics, <5% n- | 931-254-9; 927-510-4 | Skin Irrit. 2; H315 | | | |
| hexane | 921-024-6 | STOT SE 3; H336 | | | |
| | 265-151-9 | Asp. Tox. 1; H304 | | | |
| | 01-2119475514-35- | Aquatic Chronic 2; | | | |
| | XXXX | H411 | | | |
| N,N-dimethyl-p-toluidine | 99-97-8 | Acute Tox. 3; H301 | >= 0,25 - < 1 | | |
| | 202-805-4 | Acute Tox. 3; H331 | | | |
| | | Acute Tox. 3; H311 | | | |
| | | STOT RE 2; H373 | | | |
| | | Aquatic Chronic 3; | | | |
| | | H412 | | | |
| Substances with a workplace exposure limit : | | | | | |

according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator





Revision Date 24.02.2020 Version 4.0 Print Date 24.02.2020

| petroleum gases, liquefied | 68476-85-7 270-704-2 | Flam. Gas 1; H220 | >= 25 - < 40 |
|----------------------------|-------------------------|-------------------|--------------|
| | | | |

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Erythema

Dermatitis Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

Causes skin irritation.

May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

Unsuitable extinguishing : Water

Country GB 100000005178

3 / 13

according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator



Print Date 24.02.2020

Revision Date 24.02.2020 Version 4.0

media

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure.

according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator





Revision Date 24.02.2020

Version 4.0

Print Date 24.02.2020

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.

Further information on stor-

age stability

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form | Control parame- | Basis * |
|----------------------------|--|------------------|--------------------------|---------|
| | | of exposure) | ters * | |
| petroleum gases, liquefied | 68476-85-7 | TWA | 1.000 ppm 1.750 mg/m3 | GB EH40 |
| | Further information: Capable of causing cancer and/or heritable genetic damage., Carcinogenic only applies if LPG contains more than 0.1% of buta-1,3-diene. | | | |
| | | STEL | 1.250 ppm 2.180 mg/m3 | GB EH40 |

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water


Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator







Print Date 24.02.2020

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers).

Respiratory protection Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation, especially in confined areas.

limit they must use appropriate certified respirators.

When workers are facing concentrations above the exposure

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance aerosol Colour various

Odour No data available Odour Threshold No data available

Not applicable рΗ

Melting point/range / Freezing :

No data available

Boiling point/boiling range No data available

Flash point -40 °C

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit / Upper

flammability limit

7,4 %(V)

Lower explosion limit / Lower : 1,1 %(V)

flammability limit

Vapour pressure 34,6637 hPa

Relative vapour density : No data available

according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator





Print Date 24.02.2020

Revision Date 24.02.2020 Version 4.0

Density 0,67 g/cm3

Solubility(ies)

No data available Water solubility

Solubility in other solvents : No data available

Partition coefficient: n-

: No data available

octanol/water

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

: No data available Viscosity, dynamic

Viscosity, kinematic Not applicable

Explosive properties : No data available

Oxidizing properties : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator



Print Date 24.02.2020

Revision Date 24.02.2020 Version 4.0

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

N,N-dimethyl-p-toluidine:

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg

Method: Converted acute toxicity point estimate

: Acute toxicity estimate: 300 mg/kg Acute dermal toxicity

Method: Converted acute toxicity point estimate

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

Country GB 10000005178

according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator

Revision Date 24.02.2020 Version 4.0 Print Date 24.02.2020



12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

Components:

N,N-dimethyl-p-toluidine:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number

according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator



ADR : UN 1950 IMDG : UN 1950 IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS IMDG : AEROSOLS

(naphtha (petroleum))

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2 IMDG : 2.1 IATA : 2.1

14.4 Packing group

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen- : 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

Country GB 10000005178

10 / 13



according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator



14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Conditions of restriction for the following entries should be considered: petroleum gases, liquefied (Number on list 29)

None of the components are listed

(=> 0.1 %).

Not applicable

Not applicable

Not applicable

: Not applicable

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

of dangerous chemicals REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 60 %

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content:

60 %, 402 g/l

VOC content excluding water

according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator





If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

Other regulations:

75/324/EEC

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour.

H301 : Toxic if swallowed.

H304 : May be fatal if swallowed and enters airways.

H311 : Toxic in contact with skin. H315 : Causes skin irritation. H331 : Toxic if inhaled.

H336 : May cause drowsiness or dizziness.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Flam. Gas : Flammable gases Flam. Liq. : Flammable liquids Skin Irrit. : Skin irritation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADR

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

Country GB 10000005178

12 / 13

according to Regulation (EC) No. 1907/2006

Everbuild Mitre Fast Activator





Print Date 24.02.2020

Revision Date 24.02.2020 Version 4.0

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Aerosol 1 H222, H229 Calculation method
Skin Irrit. 2 H315 Calculation method
STOT SE 3 H336 Calculation method
Aquatic Chronic 2 H411 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GB / EN