Safety Data Sheet

In compliance with 'OSHA quick card' system and numbering

Section 1- IDENTIFICATION AND COMPANY

Trade Name EVERFLUX

Type & Product/Use Water Soluble Soldering Flux

Company Wiseman Industries Ltd

Hangdown Mead Business park

Top Road, Sharpthorne

West Sussex RH19 4HU

Emergency Number Tel 01277 633200

Section 2, HAZARD IDENTIFICATION

Zinc Chloride: CAS No 7646-85-7 TLV (units) 1 mg/m³ Ammonium Chloride CAS No 12125-02-9 TLV (units) 10 mg/m³

THIS PRODUCT IS NOT CLASSIFIED ACCORDING TO CLP.

Section 3 - COMPOSITION

Surfactants < 5% w/w

Emulsifying Oils

Soluble Waxes

Ammonium Chloride > 2% w/w Zinc Chloride > 4% w/w

White Oils

Inhibitors < 2% w/w

Section 4 - FIRST AID MEASURES

SKIN: Contact should be avoided. Prolonged or repeated contact can inflame or irritate the skin. In case of contact, immediate washing with plenty of soap and water is recommended. Should irritation persist seek medical advice.

EYES: Contact should be avoided. If this occurs, irrigate for at least 15 minutes under running cold tap and seek medical attention.

INHALATION: Remove to fresh air. If recovery is not immediate call doctor at once.

INGESTION: DO NOT INDUCE VOMITING. Drink Bicarbonate of Soda in water/milk/Milk of Magnesia or Washing Soda in water. Call Doctor immediately.

Section 5 - FIRE FIGHTING MEASURES

This product is water based and would not support combustion.

Section 6 - ACCIDENTAL RELEASE

In the event of spillage mop up bulk and dilute remainder to foul drain with water. Treat large spillages as industrial waste.

Section 7 - HANDLING AND STORAGE

Store in original containers and protect from extremes of temperature. Do not mix with any other material other than water as directed.

Section 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: Use in well ventilated areas to avoid the inhalation of any fumes

evolved.

HAND PROTECTION: A barrier cream is recommended – WISEMAN'S BOFANS

EYE PROTECTION: Safety goggles or face shield should be worn.

SKIN PROTECTION: Normal work ware protective clothing should be worn.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Cream coloured paste ODOUR: None pH: N/A BOILING POINT: N/A FLAMMABILITY: Does not support combustion ODOUR: None BOILING POINT: N/A FLASH POINT: N/A SOLUBILITY: Soluble in water

Section 10 - STABILITY AND REACTIVITY

This product is stable and will not cause any adverse reactions if used as directed.

Section 11 - TOXICOLOGICAL INFORMATION

INHALATION: If the soldering temperature exceeds 400°C, Zinc chloride fumes may be evolved which can cause irritation to the respiratory system.

SKIN CONTACT: Prolonged contact will inflame, irritate and burn the skin.

EYE CONTACT: Irritant and will cause inflammation.

INGESTION: May burn the mouth and cause gastrointestinal inflammation.

Section 12 - ECOLOGICAL INFORMATION

All surfactants conform to current E.E.C directives on biodegradability.

Containers may be treated as domestic waste.

Section 13 - DISPOSAL CONSIDERATIONS

In the event of spillage or leaks mop up bulk and dilute remainder to foul drain with water. For large volumes follow local authority regulations. Packaging – Rinse thoroughly with water and dispose as solid waste.

Section 14 - TRANSPORT INFORMATION

ADR - N/A CDG/CPL - N/A I.M.D.G - N/A

Section 15 - REGULATORY INFORMATION

This product is not classified as hazardous according to the Chemicals Hazard Information and Packaging for Supply (amendment) Regulations 1996.

SAFETY PHRASES –P24/25 Avoid contact with skin and eyes.

-P26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Section 16 - OTHER INFORMATION

For additional information contact WISEMAN'S Technical Services Department. The name EVERFLUX is a registered trade mark. Last Revised May 2016

WARRANTY

This product is sold only on the understanding that Wiseman Industries Ltd accepts no liability whatsoever for any loss, injury or damage direct or indirect for any purpose other than that recommended by Wiseman Industries Ltd or if the product is not used strictly in accordance with the instructions and/or directions issued with the product.