

## PRODUCT DECLARATION

We declare that >B< Press fittings may be installed with 'M' Profile jaws provided they meet the following criteria:

- The fittings are as per section 1
- The sizes are listed in section 2
- Fittings are installed with tubes listed in section 3
- Fittings are installed with machines and jaws listed in section 4
- The installation process is followed as per the instructions on the Conex Bänninger website.

### 1. PRODUCT SERIES - >B< Press Copper (P5000 Series)

### 2. SIZES - 15mm, 22mm, 28mm.

### 3. APPROVED TUBES

Size (mm)	Tube Wall Thickness (mm)					
	Copper R220		Copper R250		Copper R290	
15	1.0	-	0.7	1.0	1.0	-
22	1.0	1.2	0.9	1.1	1.0	1.5
28	-	-	-	1.2	-	1.5

### 4. COMPATIBLE TOOLS AND JAWS

15 to 28 mm				
Manufacturer	Press Machine	Press Jaws	Jaw Profile	
REMS	Mini Press	REMS – Mini*	V	Approved
			M	Compatible
	Power Press/ Akku Press	REMS – Standard*	V	Approved
			M	Compatible
Rothenberger	Compact/ Compact TT	Rothenberger Mini*	SV	Approved
			M	Compatible
	Romax 3000/4000	Rothenberger Stand- ard*	SV	Approved
			M	Compatible
NovoPress	ACO102/ ACO103	Novopress Compact PB1*	V	Approved
			M	Compatible
	ECO/ACO202	Novopress Standard PB2*	V	Approved
			M	Compatible

\*Press Jaws only, slings are not permitted.

Signed by Ged Grimes – UK & Ireland Business Unit Director



13/06/2022