28mm mixcal III group

thermostatic mixing valve





altecnic

28mm mixcal III group thermostatic mixing valve



Application

Thermostatic mixing valves are used to maintain the domestic hot water supplied to the user at a constant and safe temperature, when variations in the hot and cold water supply conditions and draw off flow rates occur.

The mixcal III group thermostatic mixing valve has been designed especially for centralised systems which demand high flow rates, for example with multiple outlets such as shower and wash basins.

Operating Principle

The controlling element of the mixing valve is a temperature sensor fully immersed in the mixed water outlet port, which expands or contracts, continuely maintaining the correct proportion of hot and cold water entering the valve.

Even when the supply pressures drop, due to draw off of hot and cold water by other users on the same system, or variations in the incoming water temperatures, the mixing valve automatically responds and maintains the mixed outlet water at the required temperature.


Connections

The valve is supplied complete with union tails which incorporate compression connections and those to the hot and cold water supplies have an integral single check valve and filter to prevent debris from entering the valve.

Construction Details

Component	Mater	ial	Grade	
Body	DZR -	chrome plated	BS EN 1982 CB752S	
Shutter	Polym	ier	PPS G40	
Springs	Stainl	ess steel		
Seals	EPDM			
Product Code	Size	Connection	Туре	
521928	28 mm	compression	Cu x Cu x Cu	

Dimensions



Prod Code	Α	В	С	D	kg
521928	Ø28	95	68	113	

Technical Data

Max. working pressure:	14 bar - Static		
	5 bar - Dynamic		
Max. inlet temperature:	90°C		

Max. Inlet temperature: 90 C

Max. inlet pressure ratio (H/C or C/H): 2:1

Accuracy: ±2°C

Setting Range: 35 to 65°C

Compression ends: BS EN 1254-2

Ky 7.6 m³/h

WRAS approved product



E & O.E

Altecnic Ltd Mustang Drive, Stafford, Staffordshire ST16 1GW T: +44 (0)1785 218200 E: sales@altecnic.co.uk
Registered in England No: 2095101

