

Flow Switches

- FSA-1** for air, heavy duty with steel cover
- FSL-1** for water, heavy duty with steel cover
- FSL-65** for water, weatherproof to IP65 with plastic cover



- Adjustable sensitivity
- Test switch
- Switch: SPDT
- 1" BSP brass connection
- Stainless steel paddles
- Set of paddles up to 6" pipe
- Connection plate for FSA-1

Power rating	120Vac	240Vac
Full load	7.4	3.7
Lock-in load	44.4	22.2
	120Vac 0.3	120Vac 0.15
Rating content	125VA, 120-240VA, 50/60Hz	
Max pressure	10.3bar (150Psi)	

Flow rates:

All flow rates indicated below are approximate and the readings have been taken with the unit mounted in a horizontal pipe. Flow rate in m³/h

Pipe size		1"	1.1/4"	1.1/2"	2"	2.1/2"	3"
Min flow adjustable	make	1.23	2.0	2.3	3.8	4.9	6.1
	break	0.74	1.1	1.4	2.1	2.4	2.5
Max flow adjustable	make	2.1	3.4	4.7	6.7	8.7	10.7
	break	1.9	2.2	4.0	4.9	7.7	9.4



Banico Controls
 Tilson Road, Manchester M23 9GF
 Tel: 0161 946 0088 Fax: 08451 700750
 e-mail: info@banico.co.uk www.banico.co.uk

