

Domestic Standard 15-60/130

Part Number: DS15

DS15 is a 3 Speed Manual Domestic Heating Circulator with a standard 1 ½” threaded connection and port-to-port distance of 130mm. Produces a maximum head of 6 meters making it the perfect replacement integrated circulator in products.

Intended for heating, cooling and air-conditioning systems, solar and geothermal energy systems. The pumps are maintenance-free for their entire service life, which confirms their high reliability. Easy to control - three constant pump speeds, easy to set using a mechanical switch. The cast iron pump volute casing is cathaphoresis coated, which acts as a protective layer that allows for dozens of times greater corrosion resistance. The pump casing is aluminium and ventilated, eliminating internal condensation and corrosion.

The Domestic Standard comes with a 3 year BritTherm™ guarantee.

*This is a replacement integrated circulator in products.

*The benchmark for the most efficient circulators is $EEI \leq 0.20$

Technical Specification

Connection Size: 1 ½”

Port to Port Distance: 130mm

Maximum Head: 6 Meters

Maximum Flow Rate: 65 Litres Per Minutes

Speed Control: 3 Fixed Speeds

System Pressure: 1.0 MPa / 10 Bar

Protection Class: IP44

Temperature Class: TF110°C

Insulation Class: F

Supplied With: Rubber Washers x2

Material: Cast Iron

Colour: Black

Weight: 2.4 kg

UKCA/CE approved