

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supersedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Resin.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
 Common Rd
 ST16 3EH
 Stafford UK
 Tel: +44 (1785) 27 26 25
 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1B - (H317)
Chronic aquatic toxicity	Category 1 - (H410)

2.2. Label Elements

Contains: Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)1,3-propanediol (4:1), 2-hydroxy-3-mercaptop, Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW



Signal word
 WARNING

Hazard statements
 H315 - Causes skin irritation

SAFETY DATA SHEET

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supersedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P264 - Wash face, hands and any exposed skin thoroughly after handling
P273 - Avoid release to the environment
P280 - Wear protective gloves and eye/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P391 - Collect spillage
P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other Hazards

No information available

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2. Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)1,3-propanediol (4:1), 2-hydroxy-3-mercaptop	-	72244-98-5	15 - 25	Skin Sens. 1B (H317) Aquatic Chronic 3 (H412)		Exempt
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	500-033-5	25068-38-6	10 - <20	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	01-2119456619-26-xxxx
Copper flakes, coated	231-159-6	7440-50-8	1- <2.5	Eye Irrit. 2 (H319) Acute Tox. 4 (H302) Acute Tox. 3 (H331) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		01-2119480154-42-xxxx

SAFETY DATA SHEET

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supersedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

				(M Factor Acute =10) (M Factor Chronic = 1)		
2,4,6-Tri(dimethylamino methyl)phenol	202-013-9	90-72-2	1- <2.5	Acute Tox. 4 (H302) Acute Tox. 4 (H312) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319)		01-2119560597-27-XXXX

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives. Burning sensation.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Full water jet. Do not scatter spilled material with high pressure water streams.

SAFETY DATA SHEET

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supersedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Product is or contains a sensitiser. May cause sensitisation by skin contact.

5.3. Advice for firefighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

7.3. Specific end use(s)

Specific Use(s)
Resin.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SAFETY DATA SHEET

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supercedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Talc 14807-96-6	-	TWA: 10 mg/m ³ TWA: 0.8 mg/m ³ STEL: 30 mg/m ³ STEL: 2.4 mg/m ³	TWA: 1 mg/m ³ STEL: 3 mg/m ³
Copper flakes, coated 7440-50-8	-	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³ STEL: 2 mg/m ³ STEL: 0.6 mg/m ³	TWA: 1 mg/m ³ TWA: 0.2 mg/m ³ STEL: 0.6 mg/m ³ STEL: 2 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)

Type	worker Short term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	8.33 mg/kg bw/d

Type	worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	8.33 mg/kg bw/d

Type	worker Short term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	12.25 mg/kg bw/d

Copper flakes, coated (7440-50-8)

Type	worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	137 mg/kg bw/d

Type	worker Short term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	273 mg/kg bw/d

Derived No Effect Level (DNEL)

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)

Type	Consumer Short term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	3.571 mg/kg bw/d

Type	Consumer Short term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	0.75 mg/kg bw/d

Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	3.571 mg/kg bw/d

SAFETY DATA SHEET

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supersedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	0.75 mg/kg bw/d

Copper flakes, coated (7440-50-8)

Type	Consumer Long term Local health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	1 mg/m ³

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	0.041 mg/kg bw/d

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.0006 mg/l
Freshwater sediment	0.996 mg/l
Marine sediment	0.0996 mg/l
Soil	0.196 mg/l

Copper flakes, coated (7440-50-8)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	7.8 µg/l
Marine water	5.2 µg/l
Microorganisms in sewage treatment	230 µg/l
Freshwater sediment	87 mg/kg dry weight
Marine sediment	676 mg/kg dry weight
Soil	65 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection

Hand protection

Wear safety glasses with side shields (or goggles).

Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Recommended Use: Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Unsuitable gloves materials: Disposable gloves. Leather. Gloves must conform to standard EN 374

Skin and body protection

Respiratory protection

Wear suitable protective clothing.

In case of inadequate ventilation wear respiratory protection. During spraying wear suitable respiratory equipment.

Recommended filter type:

Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid

SAFETY DATA SHEET

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supersedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

Appearance	Paste
Colour	metallic Brown
Odour	Sulphurous Pungent
Odour threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable	
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	No data available	
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	1.96	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	>150C	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	No information available
Softening Point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	No information available
Bulk density	No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No information available.
------------	---------------------------

10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion Data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None under normal processing.
------------------------------------	-------------------------------

10.4. Conditions to avoid

Conditions to avoid	None known based on information supplied.
---------------------	---

10.5. Incompatible materials

SAFETY DATA SHEET

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supersedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation May cause irritation of respiratory tract.

Eye contact Irritating to eyes. Causes serious eye irritation.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 14,018.00 mg/kg
ATEmix (dermal) 84,480.00 mg/kg
ATEmix (inhalation-dust/mist) 20.88 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	LD50 (Rattus) > 2000 mg/kg OECD 420	>2000 mg/Kg (Rattus)	
2,4,6-Tri(dimethylaminomethyl) phenol 90-72-2	=2169 mg/kg (Rattus)	= 1280 mg/kg (Rattus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

SAFETY DATA SHEET

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supersedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	Based on available data, the classification criteria are not met.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor	M-Factor (long-term)
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.2 mg/l 96Hr (Oncorhynchus mykiss)	-	2.7 mg/l 48hr Daphia Magna		
Copper flakes, coated 7440-50-8	EC50: 0.0426 - 0.0535mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 0.0068 - 0.0156mg/L (96h, Pimephales promelas)	-	EC50: =0.03mg/L (48h, Daphnia magna)	10	1
2,4,6-Tri(dimethylamino)methylphenol 90-72-2	EC50 (72h) = 84 mg/L (Desmodesmus subspicatus) OECD 201	CL50 (96h) = 175 mg/L (Cyprinus carpio)	-	-		

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	3.26	31
2,4,6-Tri(dimethylaminomethyl)phenol 90-72-2	0.219	-

12.4. Mobility in soil

SAFETY DATA SHEET

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supersedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or vPvB. .

Chemical name	PBT and vPvB assessment
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	The substance is not PBT / vPvB
Copper flakes, coated 7440-50-8	The substance is not PBT / vPvB PBT assessment does not apply
2,4,6-Tri(dimethylaminomethyl)phenol 90-72-2	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

Endocrine Disruptor Information

Chemical name	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	Group III Chemical	-

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.
Waste codes / waste designations according to EWC / AVV	15 01 10*: Packaging containing residues of or contaminated by dangerous substances. 16 03 03* inorganic wastes containing hazardous substances. 16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN Number	UN3077
14.2 Proper Shipping Name	Environmentally hazardous substances, solid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Copper flakes, coated)
14.3 Transport hazard class(es)	9
Labels	9
14.4 Packing Group	III
Description	UN3077, Environmentally hazardous substances, solid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Copper flakes, coated), 9, III
14.5 Environmental hazards	Yes
14.6 Special Provisions	274, 335, 601, 375
Classification Code	M7

SAFETY DATA SHEET

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supersedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

Limited Quantity (LQ)	5 kg
ADR Hazard Id (Kemmler Number)	90
IMDG	
14.1 UN number	UN3077
14.2 Proper Shipping Name	Environmentally hazardous substances, solid, n.o.s (Copper flakes, coated), Marine Pollutant
14.3 Transport hazard class(es)	9
14.4 Packing group	III
Description	UN3077, Environmentally hazardous substances, solid, n.o.s (Copper flakes, coated), 9, III, Marine Pollutant
14.5 Marine Pollutant	P.
14.6 Special Provisions	274, 335, 966, 967, 969
Limited Quantity (LQ)	5 kg
EmS-No.	F-A, S-F
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number	UN3077
14.2 Proper Shipping Name	Environmentally hazardous substances, solid, n.o.s (Copper flakes, coated)
14.3 Transport hazard class(es)	9
14.4 Packing group	III
Description	UN3077, Environmentally hazardous substances, solid, n.o.s (Copper flakes, coated), 9, III
14.5 Environmental hazards	Yes
14.6 Special Provisions	A158, A179, A97, A197
Limited Quantity (LQ)	30 kg G
ERG Code	9L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

E1 - Hazardous to the Aquatic

SAFETY DATA SHEET

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supersedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

Environment in Category Acute 1 or
Chronic 1

Ozone-depleting substances (ODS) regulation (EC) 1005/2009
Not applicable

Persistent Organic Pollutants
Not applicable

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No
Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H302 - Harmful if swallowed
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H331 - Toxic if inhaled
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H411 - Toxic to aquatic life with long lasting effects
H412 - Harmful to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals		
STOT RE	Specific target organ toxicity - Repeated exposure		
STOT SE	Specific target organ toxicity - Single exposure		
EWC:	European Waste Catalogue		

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 20-Jan-2020

Indication of changes

Revision note Not applicable.

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

SAFETY DATA SHEET

EVOSTIK PLUMBER MAIT QUICK LEAK REPAIR
Supersedes Date: 03-Jul-2019

Revision date 20-Jan-2020
Revision Number 1.01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet