

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK CARPET ADHESIVE Supercedes Date: 10-Dec-2018 Revision date 27-Aug-2019 Revision Number 2.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name Pure substance/mixture EVO-STIK CARPET ADHESIVE Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Uses advised against

Adhesives and/or sealants. None known

1.3. Details of the supplier of the safety data sheet

Company Name Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address

SDS.box-EU@bostik.com

1.4. Emergency telephone number

 United Kingdom
 +44 (1785) 272650

 Ireland
 +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Chronic aquatic toxicity	Category 2 - (H411)
Aerosols	Category 1 - (H222, H229)

2.2. Label Elements

Contains: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6, isoalkanes, <5% n-hexane, Acetone



Signal word DANGER

Hazard statements

EVO-STIK CARPET ADHESIVE

Supercedes Date: 10-Dec-2018

Revision date 27-Aug-2019 Revision Number 2.01

- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H336 May cause drowsiness or dizziness H411 - Toxic to aquatic life with long lasting effects
- H411 Toxic to aquatic life with long lasting e
- H222 Extremely flammable aerosol
- H229 Pressurised container: May burst if heated

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand
- P102 Keep out of reach of children
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P211 Do not spray on an open flame or other ignition source
- P251 Do not pierce or burn, even after use
- P261 Avoid breathing spray
- P271 Use only outdoors or in a well-ventilated area
- P273 Avoid release to the environment
- P280 Wear protective gloves and eye/face protection
- P391 Collect spillage
- P403 + P233 Store in a well-ventilated place. Keep container tightly closed
- P405 Store locked up
- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
- P501 Dispose of contents/ container to an approved waste disposal plant

Additional information

Placed on the market in aerosol containers or in containers fitted with a sealed spray attachment.

2.3. Other Hazards

No information available

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

<u>Mixtures</u>

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Acetone	200-662-2	67-64-1	15 - 25	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)		01-2119471330- 49-XXXX
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4		10 - <20	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic		01-2119475515- 33-xxxx

EVO-STIK CARPET ADHESIVE

			2 (H411) Flam. Liq. 2 (H225)	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	 5 - <10	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066)	01-2119484651- 34-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

	Change this set of the sheet to the sheet or in attendance
General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists. Consult an ophthalmologist.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water. Drink 1 or 2 glasses of water. Call a doctor or poison control centre immediately.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing.
4.2. Most important symptoms and	d effects, both acute and delayed
Symptoms	Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
4.3. Indication of any immediate m	nedical attention and special treatment needed
Note to doctors	Treat symptomatically.

SECTION 5: Firefighting measures

EVO-STIK CARPET ADHESIVE

Supercedes Date: 10-Dec-2018

Revision date 27-Aug-2019 Revision Number 2.01

5.1. Extinguishing media	—
Suitable extinguishing media	Dry chemical. Carbon dioxide (CO2). Water spray.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
5.2. Special hazards arising from the	ne substance or mixture
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.
5.3. Advice for firefighters	
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.
6.2. Environmental precautions	
Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
6.3. Methods and material for conta	ainment and cleaning up
Methods for containment	Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment.

EVO-STIK CARPET ADHESIVE

Supercedes Date: 10-Dec-2018

	Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.
7.2. Conditions for safe storage, in	cluding any incompatibilities
Storage Conditions	Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals.
7.3. Specific end use(s)	
Specific Use(s) Adhesives and/or sealants.	
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.
Other information	Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Petroleum gases, liquefied <0.1%	-	-	TWA: 1000 ppm
w/w 1,3 Butadiene			TWA: 1750 mg/m ³
68476-85-7			STEL: 1250 ppm
			STEL: 2180 mg/m ³
Acetone	TWA: 500 ppm	TWA: 500 ppm	TWA: 500 ppm
67-64-1	TWA: 1210 mg/m ³	TWA: 1210 mg/m ³	TWA: 1210 mg/m ³
	-	STEL: 1500 ppm	STEL: 1500 ppm
		STEL: 3630 mg/m ³	STEL: 3620 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)		
Acetone (67-64-1)		
Туре	Long term Systemic health effects worker	
Exposure route	Dermal	
Derived No Effect Level (DNEL)	186 mg/kg bw/d	
Туре	Short term Local health effects worker	
Exposure route	Inhalation	
Derived No Effect Level (DNEL)	2420 mg/m ³	

EVO-STIK CARPET ADHESIVE

Туре	Long term Systemic health effects worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	1210 mg/m ³

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ()		
Туре	worker Long term Systemic health effects	
Exposure route	Inhalation	
Derived No Effect Level (DNEL)	2085 mg/m³	
Туре	worker Long term Systemic health effects	
Exposure route	Dermal	
Derived No Effect Level (DNEL)	300 mg/kg bw/d	

Derived No Effect Level (DNEL)		
Acetone (67-64-1)		
Туре	Consumer Long term Systemic health effects	
Exposure route	Inhalation	
Derived No Effect Level (DNEL)	200 mg/m ³	
Туре	Consumer Long term Systemic health effects	
Exposure route	Dermal	
Derived No Effect Level (DNEL)	62 mg/kg bw/d	
Туре	Consumer Long term Systemic health effects	
Exposure route	Oral	
Derived No Effect Level (DNEL)	62 mg/kg bw/d	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ()		
Туре	Consumer Long term Systemic health effects	
Exposure route	Inhalation	
Derived No Effect Level (DNEL)	447 mg/m³	
Туре	Consumer Long term Systemic health effects	
Exposure route	Dermal	
Derived No Effect Level (DNEL)	149 mg/kg bw/d	
Туре	Consumer Long term Systemic health effects	
Exposure route	Oral	
Derived No Effect Level (DNEL)	149 mg/kg bw/d	

Predicted No Effect Concentration No information available. (PNEC)

Predicted No Effect Concentration (PNEC)	
Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

8.2. Exposure controls

EVO-STIK CARPET ADHESIVE

Supercedes Date: 10-Dec-2018

Revision date 27-Aug-2019 Revision Number 2.01

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles. Face protection shield. Gloves made of plastic or rubber. Suitable protective clothing. Skin and body protection

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Appearance Colour Odour Odour threshold	Aerosol Aerosol No information available No information available No information available
Property	Values
рН	No data available
Melting point / freezing point	No data available
Boiling point / boiling range	$= -40 \ ^{\circ}C$
Flash point	< -60 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Flammability Limit in Air	No data available
Upper flammability or explosive limits	NO data available
Lower flammability or explosive	No data available
limits	
Vapour pressure	No data available
Vapour density	No data available
Relative density	No data available
Water solubility	No data available
Solubility(ies)	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
9.2. Other information	
Solid content (%)	No information available
Softening Point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	No information available
Bulk density	No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity

No information available.

10.2. Chemical stability

Remarks • Method

EVO-STIK CARPET ADHESIVE

Supercedes Date: 10-Dec-2018

Stability	Stable under normal conditions.
Explosion Data Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.
10.3. Possibility of hazardous react	tions
Possibility of hazardous reactions	None under normal processing.
10.4. Conditions to avoid	
Conditions to avoid	Heat, flames and sparks.
10.5. Incompatible materials	
Incompatible materials	Strong acids. Strong bases. Strong oxidising agents.
10.6. Hazardous decomposition pro	oducts_
Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information	
Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Irritating to eyes. Causes serious eye irritation.
Skin contact	Causes skin irritation.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.
Symptoms related to the physical	, chemical and toxicological characteristics
Symptoms	Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	=5800 mg/kg (Rattus)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Hydrocarbons, C7, n-alkanes,	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat,

EVO-STIK CARPET ADHESIVE

Supercedes Date: 10-Dec-2018

isoalkanes, cyclics 			vapour) (OECD 403)
Hydrocarbons, C6, isoalkanes, <5% n-hexane 	>16750 mg/Kg (Rattus)	>3350 mg/Kg (Oryctolagus cuniculus) OECD 402	259354 mg/m³ (vapour) (rat OECD 403)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)	-
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 	-	-	-	EL50 (48h) =3mg/L Daphnia	-
Hydrocarbons, C6, isoalkanes, <5% n-hexane 	13.6 mg/l (Pseudokirchneriell a subcapitata)	18.3 mg/l (Oncorhynchus mykiss)	-	31.9 mg/l (Daphnia magna)	-

12.2. Persistence and degradability

EVO-STIK CARPET ADHESIVE

Persistence and degradability

No information available.

Component Information Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ()			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	83%	Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Acetone 67-64-1	-0.24	0.69
Hydrocarbons, C6, isoalkanes, <5% n-hexane 	3.6	501

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Acetone	The substance is not PBT / vPvB
67-64-1	

12.6. Other adverse effects

Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of weld containers.
Waste codes / waste designations according to EWC / AVV	16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

EVO-STIK CARPET ADHESIVE

Supercedes Date: 10-Dec-2018

SECTION 14: Transport information

Note:	The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.
Land transport (ADR/RID) 14.1 UN Number 14.2 Proper Shipping Name 14.3 Transport hazard class(es) Labels 14.4 Packing Group Description 14.5 Environmental hazards 14.6 Special Provisions Classification Code Tunnel restriction code Limited Quantity (LQ)	UN1950 Aerosols, Environmentally Hazardous 2 2.2 Not regulated UN1950, Aerosols, 2, (E), Environmentally Hazardous Yes 327, 625, 344, 190 5A (E) 1 L
IMDG 14.1 UN number 14.2 Proper Shipping Name 14.3 Transport hazard class(es) 14.4 Packing group Description 14.5 Marine Pollutant 14.6 Special Provisions Limited Quantity (LQ) EmS-No. 14.7 Transport in bulk according	UN1950 Aerosols (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics), Marine Pollutant 2.1 Not regulated UN1950, Aerosols (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics), 2.1, Marine Pollutant P 63,190, 277, 327, 344, 381, 959 See SP277 F-D, S-U to Annex II of MARPOL 73/78 and the IBC Code No information available

Air transport (ICAU-11/IATA-DGR	L
14.1 UN number	UN1950
14.2 Proper Shipping Name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards	Yes
14.6 Special Provisions	A145, A167, A802
Limited Quantity (LQ)	30 kg G
ERG Code	10L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

EVO-STIK CARPET ADHESIVE

Supercedes Date: 10-Dec-2018

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	68476-85-7	28.
		29.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS P3b - FLAMMABLE AEROSOLS E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

- H225 Highly flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H336 May cause drowsiness or dizziness
- H411 Toxic to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorisation:

LegendSECTION 8: Exposure controls/personal protectionTWATWA (time-weighted average)STELCeilingMaximum limit value*PBTPersistent, Bioaccumulative, and Toxic (PBT) ChemicalsSTOT RESTOT RESpecific target organ toxicity - Repeated exposureSTOT SESTOT SESpecific target organ toxicity - Single exposure

STEL (Short Term Exposure Limit) Skin designation

EVO-STIK CARPET ADHESIVE

Supercedes Date: 10-Dec-2018

EWC: European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By	Product Safety & Regulatory Affairs
Revision date	27-Aug-2019
Indication of changes	
Revision note	Not applicable.
Training Advice	No information available
Further information	No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet